




# PIPE FITTINGS PROCESS AND QUALITY CONTROL CHART


管件工艺流程及质量控制图








45° 弯头 Elbow



90° 弯头 Elbow



180° 弯头 Elbow

GB12459、GB/T13401


公称通径 Nominal Pipe size DN	端部外径 Outside Diameter at Bevel D		中心至端面 Center to End			中心至中心 Center to Center		背面至端面 Back to Faces			
			45° 弯头 Elbows.	90° 弯头 Elbows.		180° 弯头 Return		180° 弯头 Return			
			H	F		P		K			
			A系列 Series A	B系列 Series B	长半径 Long Radius	长半径 Long Radius	短半径 Short Radius	长半径 Long Radius	短半径 Short Radius	长半径 Long Radius	短半径 Short Radius
15	21.3	18	16	38	-	76	-	48	-		
20	26.9	25	16	38	-	76	-	51	-		
25	33.7	32	16	38	25	76	51	56	41		
32	42.4	38	20	48	32	95	64	70	52		
40	48.3	45	24	57	38	114	76	83	62		
50	60.3	57	32	76	51	152	102	106	81		
65	76.1(73)	76	40	95	64	191	127	132	100		
80	88.9	89	47	114	76	229	152	159	121		
90	101.6	-	55	133	89	267	178	184	140		
100	114.3	108	63	152	102	305	203	210	159		
125	139.7	133	79	190	127	381	254	262	197		
150	168.3	159	95	229	152	457	305	313	237		
200	219.1	219	126	305	203	610	406	414	313		
250	273.0	273	158	381	254	762	508	518	391		
300	323.9	325	189	457	305	914	610	619	467		
350	355.6	377	221	533	356	1067	711	711	533		
400	406.4	426	253	610	406	1219	813	813	610		
450	457.2	478	284	686	457	1372	914	914	686		
500	508.0	529	316	762	508	1524	1016	1016	762		
550	559	-	347	838	559						
600	610	630	379	914	610	1300	1320.8	821	1981	1981	1321
650	660	-	410	991	660	1400	1422.4	883	2134	2134	1420
700	711	720	442	1067	711	1500	1524	947	2286	2286	1524
750	762	-	473	1143	762	1600	1625.6	1010	2438	2438	1620
800	813	820	505	1219	813	1700	1727.2	1073	2591	2591	1727
850	864	-	537	1295	864	1800	1828.8	1137	2743	2743	1827
900	914	920	568	1372	914	2000	2032	1263	3048	3048	2032
950	965	-	600	1448	965	2200	2235.2	1388	3352	3352	2236
1000	1016	1020	631	1524	1016						
1050	1067	-	663	1600	1067						
1100	1118	1120	694	1676	1118						
1150	1168	-	726	1753	1168						
1200	1220	1120	758	1829	1219						

注：1) 尽可能不采用括号内数值。  
2) 优先选用A系列。


# BUTT-WELDING STRAIGHT TEES AND CROSSES

## 对焊等径三通、四通

不锈钢法兰管件 优质供应商  
Quality Supplier Of Stainless Steel  
Flange Pipe Fittings



等径三通  
Straight Outlet Tee



等径四通  
Straight Outlet Cross


GB12459、GB/T13401

公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel		中心至端面 Center to end		公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel		中心至端面 Center to end	
	D		C	M		D		C	M
	A系列 Series A	B系列 Series B				A系列 Series A	B系列 Series B		
15	21.3	18	25		450	457.2	478	343	
20	26.9	25	29		500	508.0	529	381	
25	33.7	32	38		550	559	-	419	
32	42.4	38	48		600	610	630	432	
40	48.3	45	57		650	660	-	495	
50	60.3	57	64		700	711	720	521	
65	76.1(73)	76	76		750	762	-	559	
80	88.9	89	86		800	813	820	597	
90	101.6	-	95		850	864	-	635	
100	114.3	108	105		900	914	920	673	
125	139.7	133	124		950	965	-	711	
150	168.3	159	143		1000	1016	1020	749	
200	219.1	219	178		1050	1067	-	762	711
250	273.0	273	216		1100	1118	1120	813	762
300	323.9	325	254		1150	1168	-	851	800
350	355.6	377	279		1200	1220	1120	889	838
400	406.4	426	305						


注：1) 尽可能不采用括号内数值。 2) 优先选用A系列。

# BUTT-WELDING REDUCING TEES AND CROSSES

## 对焊异径三通、四通



异径三通  
Reducing Outlet Tee



异径四通  
Reducing Cross

GB12459、GB/T13401

公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel				中心至端面 Center to End	
	D1		D2		C	M
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B		
20x15	26.9	25	21.3	18	29	29
25x20	33.7	32	26.9	25	38	38
25x15	33.7	32	21.3	18	38	38
32x25	42.4	38	33.7	32	48	48
32x20	42.4	38	26.9	25	48	48
32x15	42.4	38	21.3	18	48	48
40x32	48.3	45	42.4	38	57	57
40x25	48.3	45	33.7	32	57	57
40x20	48.3	45	26.9	25	57	57
40x15	48.3	45	21.3	18	57	57
50x40	60.3	57	48.3	45	64	60
50x32	60.3	57	42.4	38	64	57
50x25	60.3	57	33.7	32	64	51
50x20	60.3	57	26.9	25	64	44
65x50	6.1(73)	76	60.3	57	76	70
65x40	6.1(73)	76	48.3	45	76	67
65x32	6.1(73)	76	42.4	38	76	64
65x25	6.1(73)	76	33.7	32	76	57
80x65	88.9	89	76.1(73)	76	86	83
80x50	88.9	89	60.3	57	86	76
80x40	88.9	89	48.3	45	86	73
80x32	88.9	89	42.4	38	86	70
90x80	101.6	-	88.9	-	95	92
90x65	101.6	-	76.1(73)	-	95	89
90x50	101.6	-	60.3	-	95	83
90x40	101.6	-	48.3	-	95	79

公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel				中心至端面 Center to End	
	D1		D2		C	M
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B		
100x90	114.3	-	101.6	-	105	102
100x80	114.3	108	88.9	89	105	98
100x65	114.3	108	76.1(73)	76	105	95
100x50	114.3	108	60.3	57	105	89
100x40	114.3	108	48.3	45	105	86
125x100	139.7	133	114.3	108	124	117
125x90	139.7	-	101.6	-	124	114
125x80	139.7	133	88.9	89	124	111
125x65	139.7	133	76.1(73)	76	124	108
125x50	139.7	133	60.3	57	124	105
150x125	168.3	159	139.7	133	143	137
150x100	168.3	159	114.3	108	143	130
150x90	168.3	-	101.6	-	143	127
150x80	168.3	159	88.9	89	143	124
150x65	168.3	159	76.1(73)	76	143	121
200x150	219.1	219	168.3	159	178	168
200x125	219.1	219	139.7	133	178	162
200x100	219.1	219	114.3	108	178	156
200x90	219.1	219	101.6	-	178	152
250x200	273.0	273	219.1	219	216	208
250x150	273.0	273	168.3	159	216	194
200x125	273.0	273	139.7	133	216	191
200x100	273.0	273	114.3	108	216	184
300x250	323.9	325	273.0	273	254	241
300x200	323.9	325	219.1	219	254	229
300x150	323.9	325	168.3	159	254	219

# BUTT-WELDING REDUCING TEES AND CROSSES

## 对焊异径三通、四通

不锈钢法兰管件 优质供应商  
Quality Supplier Of Stainless Steel  
Flange Pipe Fittings

GB12459, GB/T13401


公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel				中心至端面 Center to End	
	D1		D2		C	M
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B		
300×125	323.9	325	139.7	133	254	216
350×300	355.6	377	323.9	325	279	270
350×250	355.6	377	273.0	273	279	257
350×200	355.6	377	219.1	219	279	248
350×150	355.6	377	168.3	159	279	238
400×350	406.4	426	355.6	377	305	305
400×300	406.4	426	323.9	325	305	295
400×250	406.4	426	273.0	273	305	283
400×200	406.4	426	219.1	219	305	273
400×150	406.4	426	168.3	159	305	264
450×400	457.2	478	406.4	426	343	330
450×350	457.2	478	355.6	377	343	330
450×300	457.2	478	323.9	325	343	321
450×250	457.2	478	273.0	273	343	308
450×200	457.2	478	219.1	219	343	298
500×450	508.0	529	457.2	478	381	368
500×400	508.0	529	406.4	426	381	356
500×350	508.0	529	355.6	377	381	356
500×300	508.0	529	323.9	325	381	346
500×250	508.0	529	273.0	273	381	333
500×200	508.0	529	219.1	219	381	324
550×500	559	-	508	-	419	406
550×450	559	-	457	-	419	394
550×400	559	-	406	-	419	381
600×550	610	-	559	-	432	432
600×500	610	630	508	530	432	432
600×450	610	630	457	480	432	419
650×600	660	-	610	-	495	483
650×550	660	-	559	-	495	470
650×500	660	-	508	-	495	457
700×650	711	-	660	-	521	521
700×600	711	720	610	630	521	508

公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel				中心至端面 Center to End	
	D1		D2		C	M
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B		
700×550	711	-	599	-	521	495
750×700	762	-	711	-	559	546
750×650	762	-	660	-	559	546
750×600	762	-	610	-	559	533
800×750	813	-	762	-	597	584
800×700	813	820	711	720	597	572
800×650	813	-	660	-	597	572
850×800	864	-	813	-	635	622
850×750	864	-	762	-	635	610
850×700	864	-	711	-	635	597
900×850	914	-	864	-	673	660
900×800	914	920	813	820	673	648
900×750	914	-	762	-	673	635
950×900	965	-	914	-	711	711
950×850	965	-	864	-	711	698
950×800	965	-	813	-	711	686
1000×950	1016	-	965	-	749	749
1000×900	1016	1020	914	920	749	737
1000×850	1016	-	864	-	749	724
1050×1000	1067	-	1016	-	762	711
1050×950	1067	-	965	-	762	711
1050×900	1067	-	914	-	762	711
1100×1050	1118	-	1067	-	813	762
1100×1000	1118	1120	1016	1020	813	749
1100×950	1118	-	965	-	813	737
1150×1100	1168	-	1118	-	851	800
1150×1050	1168	-	1067	-	851	787
1150×1000	1168	-	1016	-	851	775
1200×1150	1220	-	1168	-	889	838
1200×1100	1220	1220	1118	1120	889	838
1200×1050	1220	-	1067	-	889	813


注：1) 尽可能不采用括号内数值。 2) 优先选用A系列。

# BUTT-WELDING CONCENTRIC & ECCENTRIC REDUCERS

对焊同心、偏心异径管



同心大小头  
Concentric Reducers



偏心大小头  
Eccentric Reducers

GB12459, GB/T13401

公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel				长度 End to End L
	D1		D2		
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B	
20x15	26.9	25	21.3	18	38
25x20	33.7	32	26.9	25	51
25x15	33.7	32	21.3	18	51
32x25	42.4	38	33.7	32	51
32x20	42.4	38	26.9	25	51
32x15	42.4	38	21.3	18	51
40x32	48.3	45	42.4	38	64
40x25	48.3	45	33.7	32	64
40x20	48.3	45	26.9	25	64
40x15	48.3	45	21.3	18	64
50x40	60.3	57	48.3	45	76
50x32	60.3	57	42.4	38	76
50x25	60.3	57	33.7	32	76
50x20	60.3	57	26.9	25	76
65x50	76.1(73)	76	60.3	57	89
65x40	76.1(73)	76	48.3	45	89
65x32	76.1(73)	76	42.4	38	89
65x25	76.1(73)	76	33.7	32	89
80x65	88.9	89	76.1(73)	76	89
80x50	88.9	89	60.3	57	89
80x40	88.9	89	48.3	45	89
80x32	88.9	89	42.4	38	89
90x80	101.6	-	88.9	-	102
90x65	101.6	-	76.1(73)	-	102
90x50	101.6	-	60.3	-	102
90x40	101.6	-	48.3	-	102
90x32	101.6	-	42.4	-	102
100x90	114.3	-	101.6	-	102
100x80	114.3	108	88.9	89	102
100x65	114.3	108	76.1(73)	76	102
100x50	114.3	108	60.3	57	102
100x40	114.3	108	48.3	45	102
125x100	139.7	133	114.3	108	127
125x90	139.7	-	101.6	-	127
125x80	139.7	133	88.9	89	127

公称通径 Nominal Pipe Size DN	端部外径 Outside Diameter at Bevel				长度 End to End L
	D1		D2		
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B	
125x65	139.7	133	76.1(73)	76	127
125x50	139.7	133	60.3	57	127
150x125	168.3	159	139.7	133	140
150x100	168.3	159	114.3	108	140
150x90	168.3	-	101.6	-	140
150x80	168.3	159	88.9	89	140
150x65	168.3	159	76.1(73)	76	140
200x150	219.1	219	168.3	159	152
200x125	219.1	219	139.7	133	152
200x100	219.1	219	114.3	108	152
200x90	219.1	-	101.6	-	152
250x200	273.0	273	219.1	219	178
250x150	273.0	273	168.3	159	178
250x125	273.0	273	139.7	133	178
250x100	273.0	273	114.3	108	178
300x250	323.9	325	273.0	273	203
300x200	323.9	325	219.1	219	203
300x150	323.9	325	168.3	159	203
300x125	323.9	325	139.7	133	203
350x300	355.6	377	323.9	325	330
350x250	355.6	377	273.0	273	330
350x200	355.6	377	219.1	219	330
350x150	355.6	377	168.3	159	330
400x350	406.4	426	355.6	377	356
400x300	406.4	426	323.9	325	356
400x250	406.4	426	273.0	273	356
400x200	406.4	426	219.1	219	356
450x400	457.2	478	406.4	426	381
450x350	457.2	478	355.6	377	381
450x300	457.2	478	323.9	325	381
450x250	457.2	478	273.0	273	381
500x450	508.0	529	457.2	478	508
500x400	508.0	529	406.4	426	508
500x350	508.0	529	355.6	377	508
500x300	508.0	529	323.9	325	508

# BUTT-WELDING CONCENTRIC & ECCENTRIC REDUCERS

对焊同心、偏心异径管

不锈钢法兰管件 优质供应商

Quality Supplier Of Stainless Steel  
Flange Pipe Fittings


GB12459, GB/T13401

公称通径 Nominal Pipe size DN	端部外径 Outside Diameter at Bevel				长度 End to End L
	D1		D2		
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B	
550x500	559	-	508	-	508
550x450	559	-	457	-	508
550x400	559	-	406	-	508
550x350	559	-	356	-	508
600x550	610	-	559	-	508
600x500	610	630	508	530	508
600x450	610	630	457	480	508
600x400	610	630	406	426	508
650x600	660	-	610	-	610
650x550	660	-	559	-	610
650x500	660	-	508	-	610
650x450	660	-	457	-	610
700x650	711	-	660	-	610
700x600	711	720	610	630	610
700x550	711	-	559	-	610
700x500	711	720	508	530	610
750x700	762	-	711	-	610
750x650	762	-	660	-	610
750x600	762	-	610	-	610
750x550	762	-	559	-	610
800x750	813	-	762	-	610
800x700	813	820	711	720	610
800x650	813	-	660	-	610
800x600	813	820	610	630	610
850x800	864	-	813	-	610
850x750	864	-	762	-	610
850x700	864	-	711	-	610
850x650	864	-	660	-	610


公称通径 Nominal Pipe size DN	端部外径 Outside Diameter at Bevel				长度 End to End L
	D1		D2		
	A系列 Series A	B系列 Series B	A系列 Series A	B系列 Series B	
900x850	914	-	864	-	610
900x800	914	920	813	820	610
900x750	914	-	762	-	610
900x700	914	920	711	720	610
950x900	965	-	914	-	610
950x850	965	-	864	-	610
950x800	965	-	813	-	610
950x750	965	-	762	-	610
1000x950	1016	-	965	-	610
1000x900	1016	1020	914	920	610
1000x850	1016	-	864	-	610
1000x800	1016	1020	813	820	610
1050x1000	1067	-	1016	-	610
1050x950	1067	-	965	-	610
1050x900	1067	-	914	-	610
1050x850	1067	-	864	-	610
1100x1050	1118	-	1067	-	610
1100x1000	1118	1120	1016	1020	610
1100x950	1118	-	965	-	610
1100x900	1118	1120	914	920	610
1150x1100	1168	-	1118	-	711
1150x1050	1168	-	1067	-	711
1150x1000	1168	-	1016	-	711
1150x950	1168	-	965	-	711
1200x1150	1220	-	1168	-	711
1200x1100	1220	1220	1118	1120	711
1200x1050	1220	-	1067	-	711
1200x1000	1220	1220	1016	1020	711

注: 1) 尽可能不采用括号内数值。 2) 优先选用A系列。


规定的对焊管件端坡口的结构型式 GB12459 GB/T13401  
End Preparation of Butt-welding Fittings to GB 12459&GB/T 13401



(a) 壁厚 ≤ 22



(b) 壁厚 ≥ 22




翻边接头  
Lap joint stub ends

尺寸/SE对焊环 Size SE butt welding ring

公称通径 Nominal Pipe size DN(in)	端部外径 Outside Diameter at Bevel D		长度 Length	圆角半径 Radius of fillet	搭线直径 Diameter of Lap
	A系列 SeriesA	B系列 SeriesB	L	R	G
15	21.3	18	38	2	46
20	26.9	25	40	2	56
25	33.7	32	40	3	65
32	42.4	38	42	3	76
40	48.3	45	45	3	84
50	60.3	57	48	3	99
65	76.1	76	48	3	118
80	88.9	89	50	4	132
100	114.3	108	52	4	156
125	139.7	133	55	4	184
150	168.3	159	55	4	211
200	219.1	219	62	5	266
250	273	273	70	5	319
300	323.9	325	78	5	370
350	355.6	377	82	5	429
400	406.4	426	85	5	480
450	457	478	87	5	548
500	508	529	90	6	609
600	610	630	95	6	720

注：1、本表尺寸适用对焊环松套钢制管法兰（HG20599-97）PN1.6Mpa。  
2、客户要求不同压力及型号，请在合同上注册。



GB 12459、GB/T 13401


公称通径 Nominal Pipe size DN	端部外径D Outside Diameter at Bevel		全长 Length		对尺寸E的 限制厚度 Limiting Wall Thickness for Length E
	A系列 Series A	B系列 Series B	E	E <sub>1</sub>	
15	21.3	18	25	-	-
20	26.9	25	25	-	-
25	33.7	32	38	-	-
32	42.4	38	38	-	-
40	48.3	45	38	-	-
50	60.3	57	38	44	5.5
65	76.1(73)	76	38	51	7.0
80	88.9	89	51	64	7.6
90	101.6	-	64	76	8.1
100	114.3	108	64	76	8.6
125	139.7	133	76	89	9.5
150	168.3	159	89	102	11.0
200	219.1	219	102	127	12.7
250	273.0	273	127	152	12.7
300	323.9	325	152	178	12.7
350	355.6	377	165	191	12.7
400	406.4	426	178	203	12.7
450	457.2	478	203	229	12.7
500	508.0	529	229	254	12.7

公称通径 Nominal Pipe size DN	端部外径D Outside Diameter at Bevel		全长 Length
	A系列 Series A	B系列 Series B	
550	559	-	254
600	610	630	267
650	660	-	267
700	711	720	267
750	762	-	267
800	813	820	267
850	864	-	267
900	914	920	267
950	965	-	305
1000	1016	1020	305
1050	1067	-	305
1100	1118	1120	343
1150	1168	-	343
1200	1220	1220	343


注：1) DN600的管帽，当壁厚超过13mm时其E值改为305mm。  
2) 尽可能不采用括号内的数值。  
3) 管帽的全长不大于限制厚度时为E，超过限制厚度为E<sub>1</sub>。

# BUTT-WELDING LONG AND SHORT RADIUS ELBOWS

## 对焊长、短半径弯头



45° 弯头 Elbow



90° 弯头 Elbow


ASME B16.9, B16.28

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel OD		中心至端面 Center - to - end							
			A				B			
			长半径 Long Radius		短半径 Short Radius		长半径 Long Radius		短半径 Short Radius	
			IN	MM	IN	MM	IN	MM	IN	MM
1/2	0.84	21.3	1.5	38	-	-	0.62	16	-	-
3/4	1.05	26.7	1.12	29	-	-	0.44	11	-	-
1	1.32	33.4	1.5	38	1	25	0.88	22	0.41	10
1 1/4	1.66	42.2	1.88	48	1.25	32	-	25	0.52	13
1 1/2	1.9	48.3	2.25	57	1.5	38	1.12	29	0.62	16
2	2.38	60.3	3	76	2	51	1.38	35	0.83	21
2 1/2	2.88	73.0	3.75	95	2.5	64	1.75	44	1.04	26
3	3.5	88.9	4.5	114	3	76	2	51	1.24	32
3 1/2	4	101.6	5.25	133	3.5	89	2.25	57	1.45	37
4	4.5	114.3	6	152	4	102	2.5	64	1.66	42
5	5.56	141.3	7.5	190	5	127	3.12	79	2.07	53
6	6.62	168.3	9	229	6	152	3.75	95	2.50	63
8	8.62	219.1	12	305	8	203	5	127	3.31	84
10	10.75	273.0	15	381	10	254	6.25	159	4.14	105
12	12.75	323.8	18	457	12	305	7.5	190	4.97	126
14	14	355.6	21	533	14	356	8.75	222	5.80	147
16	16	406.4	24	610	16	406	10	254	6.63	168
18	18	457	27	686	18	457	11.25	286	7.46	189
20	20	508	30	762	20	508	12.5	318	8.28	210
22	22	559	33	838	22	559	13.5	343	9.11	232
24	24	610	36	914	24	610	15	381	9.94	253
26	26	660	39	991	26	660	16	405	10.77	274
28	28	711	42	1067	28	711	17.25	438	11.60	295
30	30	762	45	1143	30	762	18.5	470	12.43	316
32	32	813	48	1219	32	813	19.75	502	14.89	378
34	34	864	51	1295	34	864	21	533	14.08	358
36	36	914	54	1372	36	914	22.25	565	14.91	379
38	38	965	57	1448	38	965	23.62	600	15.74	400
40	40	1016	60	1524	40	1016	24.88	632	16.57	421
42	42	1067	63	1600	42	1067	26	660	17.40	442
44	44	1118	66	1676	44	1118	27.38	695	18.23	463
46	46	1168	69	1753	46	1168	28.62	727	19.05	484
48	48	1219	72	1829	48	1219	29.88	759	19.88	505

# BUTT-WELDING LONG AND SHORT RADIUS ELBOWS


对焊长、短半径弯头

不锈钢法兰管件 优质供应商  
Quality Supplier Of Stainless Steel  
Flange Pipe Fittings



ASME B16.9, B16.28

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel OD		中心至端面 Center - to - end				长度 End - to - end			
			180°弯头 Returns				180°弯头 Returns			
			O				K			
			长半径 Long Radius		短半径 Short Radius		长半径 Long Radius		短半径 Short Radius	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
1/2	0.84	21.3	3	76	-	-	1.88	48	-	-
3/4	1.05	26.7	2.25	57	-	-	1.69	43	-	-
1	1.32	33.4	3	76	2	51	2.19	56	1.62	41
1 1/4	1.66	42.2	3.75	95	5	64	2.75	70	2.06	52
1 1/2	1.9	48.3	4.5	114	3	76	3.25	83	2.44	62
2	2.38	60.3	6	152	4	102	4.19	106	3.19	81
2 1/2	2.88	73.0	7.5	190	5	127	5.19	132	3.94	100
3	3.5	88.9	9	229	6	152	6.25	159	4.75	121
3 1/2	4	101.6	10.5	267	7	178	7.25	184	5.5	140
4	4.5	114.3	12	305	8	203	8.25	210	6.25	159
5	5.56	141.3	15	381	10	254	10.31	262	7.75	197
6	6.62	168.3	18	457	12	305	12.31	313	9.31	237
8	8.62	219.1	24	610	16	406	16.31	414	12.31	313
10	10.75	273.0	30	762	20	508	20.38	518	15.38	391
12	12.75	323.8	36	914	24	610	24.38	619	18.38	467
14	14	355.6	42	1067	28	711	28	711	21	533
16	16	406.4	48	1219	32	813	32	813	24	610
18	18	457	54	1372	36	914	36	914	27	686
20	20	508	60	1524	40	1016	40	1016	30	762
22	22	559	66	1676	44	1118	44	1118	33	838
24	24	610	72	1829	48	1219	48	1219	36	914



ASME B16.9


公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel OD		中心至端面 Center - to - end				长度 End - to - end					
			等径三通 Straight Outlet Tees				管帽 Caps					
			C		M(1)		长度 Length(2) E		对尺寸E的限制厚度 Limiting Wall Thickness For Length "E"		长度 Length(3) E1	
			IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
1/2	0.84	21.3	1	25	1	25	1	25	0.18	4.58	1	25
3/4	1.05	26.7	1.12	29	1.12	29	1	25	0.15	3.81	1	25
1	1.32	33.4	1.5	38	1.5	38	1.5	38	0.18	4.57	1.5	38
1 1/4	1.66	42.2	1.88	48	1.88	48	1.5	38	0.19	4.83	1.5	38
1 1/2	1.9	48.3	2.25	57	2.25	57	1.5	38	0.2	5.08	1.5	38
2	2.38	60.3	2.5	64	2.5	64	1.5	38	0.22	5.59	1.75	44
2 1/2	2.88	73.0	3	76	3	76	1.5	38	0.28	7.11	2	51
3	3.5	88.9	3.38	86	3.38	86	2	51	0.3	7.62	2.5	64
3 1/2	4	101.6	3.75	95	3.75	95	2.5	64	0.32	8.13	3	76
4	4.5	114.3	4.12	105	4.12	105	2.5	64	0.37	8.64	3	76
5	5.56	141.3	4.88	124	4.88	124	3	76	0.38	9.65	3.5	89
6	6.62	168.3	5.62	143	5.62	143	3.5	89	0.43	10.92	4	102
8	8.62	219.1	7	178	7	178	4	102	0.5	12.7	5	127
10	10.75	273.0	8.5	216	8.5	216	5	127	0.5	12.7	6	152
12	12.75	323.8	10	254	10	254	6	152	0.5	12.7	7	178
14	14	355.6	11	279	11	279	6.5	165	0.5	12.7	7.5	191
16	16	406.4	12	305	12	305	7	178	0.5	12.7	8	203
18	18	457.2	13.5	343	13.5	343	8	203	0.5	12.7	9	229
20	20	508	15	381	15	381	9	229	0.5	12.7	10	254
22	22	558.8	16.5	419	16.5	419	10	254	0.5	12.7	10	254
24	24	609.6	17	432	17	432	10.5	267	0.5	12.7	12	305
26	26	660.4	19.5	495	19.5	495	10.5	267	-	-	-	-
28	28	711.2	20.2	521	20.2	521	10.5	267	-	-	-	-
30	30	762	22	559	22	559	10.5	267	-	-	-	-
32	32	812.8	23.5	597	23.5	597	10.5	267	-	-	-	-
34	34	863.6	25	635	25	635	10.5	267	-	-	-	-
36	36	914.4	26.5	673	26.5	673	10.5	267	-	-	-	-
38	38	965.2	28	711	28	711	12	305	-	-	-	-
40	40	1016	29.5	749	29.5	749	12	305	-	-	-	-
42	42	1066.8	30	762	28	711	12	305	-	-	-	-
44	44	1117.6	32	813	30	762	13.5	343	-	-	-	-
46	46	1168.4	33.5	851	31.5	800	13.5	343	-	-	-	-
48	48	1219.2	35	889	33	838	13.5	343	-	-	-	-

NOTES:

- (1) Outlet dimension M for NPS 26 and larger is recommended but not required.
- (2) Length E applies for thickness not exceeding that given in column "Limiting Wall Thickness for Length E"
- (3) Length E1 applies for thickness greater than that given in column "Limiting Wall Thickness for Length E" for NPS 24 and smaller.

# LAP JOINT STUB ENDS 翻边接头

不锈钢法兰管件 优质供应商  
Quality Supplier Of Stainless Steel  
Flange Pipe Fittings




ASME B16.9 MSS SP-43

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel OD		端部外径 Outside Diameter of Barrel				端部外径 Diameter OF LAP G (Nominal&Max)	
	IN	MM	Max		Min		IN	MM
			IN	MM	IN	MM		
1/2	0.84	21.3	0.896	22.8	0.809	20.5	1.38	35
3/4	1.05	26.7	1.106	28.1	1.019	25.9	1.69	43
1	1.32	33.4	1.376	35	1.284	32.6	2	51
1 1/4	1.65	42.2	1.716	43.6	1.629	41.4	2.5	64
1 1/2	1.9	48.3	1.965	49.9	1.869	47.5	2.88	73
2	2.38	60.3	2.456	62.4	2.344	59.5	3.62	92
2 1/2	2.88	70.0	2.966	75.3	2.844	72.2	4.12	106
3	3.5	88.9	3.596	91.3	3.469	88.1	5	127
3 1/2	4	110.6	4.096	104	3.969	100.8	5.5	140
4	4.5	114.3	4.593	116.7	4.469	113.5	6.19	157
5	5.56	141.3	5.683	144.3	5.532	140.5	7.31	185
6	6.62	168.3	6.743	171.3	6.594	167.5	8.5	218
8	8.62	219.1	8.743	222.1	8.594	218.3	10.62	270
10	10.75	273.0	10.913	277.2	10.719	272.3	12.75	324
12	12.75	323.8	12.913	328	12.719	323.1	15	381
14	14	355.6	14.17	359.9	13.969	354.8	16.25	413
16	16	406.4	16.18	411	15.969	405.6	18.5	370
18	18	457	18.19	462	17.969	456	21	533
20	20	508	20.24	514	19.969	507	23	584
22	22	559	22.24	565	21.969	558	25.25	641
24	24	610	24.24	616	23.969	609	27.25	692


公称通径 Nominal Pipe Size (NPS)	长度 Length F				半径 Radius R			
	ASME Long		ASME Short & MSS		MSS Type A & ASME (Nominal&Max)		MSS Type B (Max)	
	IN	MM	IN	MM	IN	MM	IN	MM
1/2	3	76	2	51	0.12	1.38	0.03	0.8
3/4	3	76	2	51	0.12	1.69	0.03	0.8
1	4	102	2	51	0.12	2	0.03	0.8
1 1/4	4	102	2	51	0.19	2.5	0.03	0.8
1 1/2	4	102	2	51	0.25	2.88	0.03	0.8
2	6	152	2.5	64	0.31	3.62	0.03	0.8
2 1/2	6	152	2.5	64	0.31	4.12	0.03	0.8
3	6	152	2.5	64	0.38	5	0.03	0.8
3 1/2	6	152	3	76	0.38	5.5	0.03	0.8
4	6	152	3	76	0.44	6.19	0.03	0.8
5	8	203	3	76	0.44	7.31	0.06	1.5
6	8	203	3.5	89	0.5	8.5	0.06	1.5
8	8	203	4	102	0.5	10.62	0.06	1.5
10	10	254	5	127	0.5	12.75	0.06	1.5
12	10	254	6	152	0.5	15	0.06	1.5
14	12	305	6	152	0.5	16.25	0.06	1.5
16	12	305	6	152	0.5	18.5	0.06	1.5
18	12	305	6	152	0.5	21	0.06	1.5
20	12	305	6	152	0.5	23	0.06	1.5
22	12	305	6	152	0.5	25.25	0.06	1.5
24	12	305	6	152	0.5	27.25	0.06	1.5

# REDUCING TEES AND CONCENTRIC & ECCENTRIC REDUCERS


异径三通和同心，偏心异径管



异径三通  
Reducing Outlet Tee



同心大小头  
Concentric Reducers



偏心大小头  
Eccentric Reducers

## ASME B16.9


公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel				中心至端面 Center - to - end				长度 End - to - end	
	OD <sub>1</sub>		OD <sub>2</sub>		C		M		H	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
3/4x1/2	1.05	26.7	0.84	21.3	1.12	29	1.12	29	1.5	38
1x3/4	1.32	33.4	1.05	26.7	1.5	38	1.5	38	2	51
1x1/2	1.32	33.4	0.84	21.3	1.5	38	1.5	38	2	51
1 1/4x1	1.66	42.2	1.32	33.4	1.88	48	1.88	48	2	51
1 1/4x3/4	1.66	42.2	1.05	26.7	1.88	48	1.88	48	2	51
1 1/4x1/2	1.66	42.2	0.84	21.3	1.88	48	1.88	48	2	51
1 1/2x1 1/4	1.9	42.2	1.66	42.2	2.25	57	2.25	57	2.5	64
1 1/2x1	1.9	48.3	1.32	33.4	2.25	57	2.25	57	2.5	64
1 1/2x3/4	1.9	48.3	1.05	26.7	2.25	57	2.25	57	2.5	64
1 1/2x1/2	1.9	48.3	0.84	21.3	2.25	57	2.25	57	2.5	64
2x1 1/2	2.38	60.3	1.9	48.3	2.5	64	2.38	60	3	76
2x1 1/4	2.38	60.3	1.66	42.2	2.5	64	2.25	57	3	76
2x1	2.38	60.3	1.32	33.4	2.5	64	2	51	3	76
2x3/4	2.38	60.3	1.05	26.7	2.5	64	1.75	44	3	76
2x1/2	2.38	60.3	0.84	21.3	2.5	64	*	*	3	76
2 1/2x2	2.88	73	2.38	60.3	3	76	2.75	70	3.5	89
2 1/2x1 1/2	2.88	73	1.9	48.3	3	76	2.62	67	3.5	89
2 1/2x1 1/4	2.88	73	1.66	42.2	3	76	2.5	64	3.5	89
2 1/2x1	2.88	73	1.32	33.4	3	76	2.25	57	3.5	89
2 1/2x3/4	2.88	73	1.05	26.7	3	76	*	*	3.5	89
2 1/2x1/2	2.88	73	0.84	21.3	3	76	*	*	3.5	89
3x2 1/2	3.5	88.9	2.88	73	3.38	86	3.25	83	3.5	89
3x2	3.5	88.9	2.38	60.3	3.38	86	3	76	3.5	89
3x1 1/2	3.5	88.9	1.9	48.3	3.38	86	2.88	73	3.5	89
3x1 1/4	3.5	88.9	1.66	42.2	3.38	86	2.75	70	3.5	89
3x1	3.5	88.9	1.32	33.4	3.38	86	*	*	3.5	89
3x3/4	3.5	88.9	1.05	26.7	3.38	86	*	*	3.5	89
3x1/2	3.5	88.9	0.84	21.3	3.38	86	*	*	3.5	89
3 1/2x3	4	101.6	3.5	88.9	3.75	95	3.62	92	4	102
3 1/2x2 1/2	4	101.6	2.88	73	3.75	95	3.5	89	4	102
3 1/2x2	4	101.6	2.38	60.3	3.75	95	3.25	83	4	102
3 1/2x1 1/2	4	101.6	1.9	48.3	3.75	95	3.12	79	4	102
3 1/2x1 1/4	4	101.6	1.66	42.2	3.75	95	*	*	4	102
4x3 1/2	4.5	114.3	4	101.6	4.12	105	4	102	4	102
4x3	4.5	114.3	3.5	88.9	4.12	105	3.88	98	4	102
4x2 1/2	4.5	114.3	2.88	73	4.12	105	3.75	95	4	102
4x2	4.5	114.3	2.38	60.3	4.12	105	3.5	89	4	102
4x1 1/2	4.5	114.3	1.9	48.3	4.12	105	3.38	86	4	102
4x1 1/4	4.5	114.3	1.66	42.2	4.12	105	*	*	4	102
4x1	4.5	114.3	1.32	33.4	4.12	105	*	*	4	102

# REDUCING TEES AND CONCENTRIC & ECCENTRIC REDUCERS


异径三通和同心，偏心异径管

不锈钢法兰管件 优质供应商


Quality Supplier Of Stainless Steel  
Flange Pipe Fittings



异径三通  
Reducing Outlet Tee



同心大小头  
Concentric Reducers



偏心大小头  
Eccentric Reducers


## ASME B16.9

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel				中心至端面 Center - to - end				长度 End - to - end	
	OD <sub>1</sub>		OD <sub>2</sub>		C		M(1)		H	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
5x4	5.56	141.3	4.5	114.3	4.88	124	4.62	117	5	127
5x3 1/3	5.56	141.3	4	101.6	4.88	124	4.5	114	5	127
5x3	5.56	141.3	3.5	88.9	4.88	124	4.38	111	5	127
5x2 1/2	5.56	141.3	2.88	73	4.88	124	4.25	108	5	127
5x2	5.56	141.3	2.38	60.3	4.88	124	4.12	105	5	127
5x1 1/2	5.56	141.3	1.9	48.3	4.88	124	*	*	5	127
5x1 1/4	5.56	141.3	1.66	42.2	4.88	124	*	*	5	127
6x5	6.62	168.3	5.56	141.3	5.62	143	5.38	137	5.5	140
6x4	6.62	168.3	4.5	114.3	5.62	143	5.12	130	5.5	140
6x3 1/2	6.62	168.3	4	101.6	5.62	143	5	127	5.5	140
6x3	6.62	168.3	3.5	88.9	5.62	143	4.88	124	5.5	140
6x2 1/2	6.62	168.3	2.88	73	5.62	143	4.75	121	5.5	140
6x2	6.62	168.3	2.38	60.3	5.62	143	*	*	5.5	140
8x6	8.62	219.1	6.62	168.3	7	178	6.62	168	6	152
8x5	8.62	219.1	5.56	141.3	7	178	6.38	162	6	152
8x4	8.62	219.1	4.5	114.3	7	178	6.12	156	6	152
8x3 1/2	8.62	219.1	4	101.6	7	178	6	152	6	152
8x3	8.62	219.1	3.5	88.9	7	178	*	*	6	152
10x8	10.75	273	8.62	219.1	8.5	216	8	203	7	178
10x6	10.75	273	6.62	168.3	8.5	216	7.62	194	7	178
10x5	10.75	273	5.56	141.3	8.5	216	7.5	191	7	178
10x4	10.75	273	4.5	114.3	8.5	216	7.25	184	7	178
10x3	10.75	273	3.5	88.9	8.5	216	*	*	7	178
12x10	12.75	323.8	10.75	273	10	254	9.5	241	8	203
12x8	12.75	323.8	8.62	219.1	10	254	9	229	8	203
12x6	12.75	323.8	6.62	168.3	10	254	8.62	219	8	203
12x5	12.75	323.8	5.56	141.3	10	254	8.5	216	8	203
12x4	12.75	323.8	4.5	114.3	10	254	*	*	8	203
14x12	14	355.6	12.75	323.8	11	279	10.62	270	13	330
14x10	14	355.6	10.75	273	11	279	10.12	257	13	330
14x8	14	355.6	8.62	219.1	11	279	9.75	248	13	330
14x6	14	355.6	6.62	168.3	11	279	9.38	238	13	330
14x5	14	355.6	5.56	141.3	11	279	*	*	13	330
16x14	16	406.4	14	355.6	12	305	12	305	14	356
16x12	16	406.4	12.75	323.8	12	305	11.62	295	14	356
16x10	16	406.4	10.75	273	12	305	11.12	283	14	356
16x8	16	406.4	8.62	219.1	12	305	10.75	273	14	356
16x6	16	406.4	6.62	168.3	12	305	10.38	264	14	356
18x16	18	457	16	406.4	13.5	343	13	330	15	381


NOTE:(1)Outlet dimensions M for run sizes NPS 14 and larger is recommended but not required.

# REDUCING TEES AND CONCENTRIC & ECCENTRIC REDUCERS


异径三通和同心，偏心异径管



异径三通  
Reducing Outlet Tee



同心大小头  
Concentric Reducers



偏心大小头  
Eccentric Reducers

## ASME B16.9

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel				中心至端面 Center - to - end				长度 End - to - end	
	OD <sub>1</sub>		OD <sub>2</sub>		C		M(1)		H	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
18x14	18	457	14	355.6	13.5	343	13	330	15	381
18x12	18	457	12.75	323.8	13.5	343	12.62	321	15	381
18x10	18	457	10.75	273	13.5	343	12.12	308	5	381
18x8	18	457	8.62	219.1	13.5	343	11.75	298	15	381
20x18	20	508	18	457.2	15	381	14.5	368	20	508
20x16	20	508	16	406.4	15	381	14	356	20	508
20x14	20	508	14	355.6	15	381	14	356	20	508
20x12	20	508	12.75	323.8	15	381	13.62	346	20	508
20x10	20	508	10.75	273	15	381	13.12	333	20	508
20x8	20	508	8.62	219.1	15	381	12.75	324	20	508
22x20	22	559	20	508	16.5	419	16	406	20	508
22x18	22	559	18	457.2	16.5	419	15.5	394	20	508
22x16	22	559	16	406.4	16.5	419	15	381	20	508
22x14	22	559	14	355.6	16.5	419	15	381	20	508
22x12	22	559	12.75	323.8	16.5	419	14.62	371	20	508
22x10	22	559	10.75	273	16.5	419	14.12	359	20	508
24x22	24	610	22	558.8	17	432	17	432	20	508
24x20	24	610	20	508	17	432	17	432	20	508
24x18	24	610	18	457.2	17	432	16.5	419	20	508
22x16	24	610	16	406.4	17	432	16	406	20	508
22x14	24	610	14	355.6	17	432	16	405	20	508
24x12	24	610	12.75	323.8	17	432	15.62	397	20	508
24x10	24	610	10.75	273	17	432	15.12	384	20	508
26x24	26	660	24	609.6	19.5	495	19	483	24	610
26x22	26	660	22	558.8	19.5	495	18.5	470	24	610
26x20	26	660	20	508	19.5	495	18	457	24	610
26x18	26	660	18	457.2	19.5	495	17.5	444	24	610
26x16	26	660	16	406.4	19.5	495	17	432	24	610
26x14	26	660	14	355.6	19.5	495	17	432	24	610
26x12	26	660	12.75	323.8	19.5	495	16.62	422	24	610
28x26	28	711	26	660.4	20.5	521	20.5	521	24	610
28x24	28	711	24	609.6	20.5	521	20	508	24	610
28x22	28	711	22	558.8	20.5	521	19.5	495	24	610
28x20	28	711	20	508	20.5	521	19	483	24	610
28x18	28	711	18	457.2	20.5	521	18.5	470	24	610
28x16	28	711	16	406.4	20.5	521	18	457	24	610
28x14	28	711	14	355.6	20.5	521	18	457	24	610
28x12	28	711	12.75	323.8	20.5	521	17.62	448	24	610
30x28	30	762	28	711.2	22	559	21.5	546	24	610


NOTE:(1)Outlet dimensions M for run sizes NPS 14 and larger is recommended but not required.

# REDUCING TEES AND CONCENTRIC & ECCENTRIC REDUCERS


异径三通和同心，偏心异径管

不锈钢法兰管件 优质供应商


Quality Supplier Of Stainless Steel  
Flange Pipe Fittings



异径三通  
Reducing Outlet Tee



同心大小头  
Concentric Reducers



偏心大小头  
Eccentric Reducers


## ASME B16.9

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel				中心至端面 Center - to - end				长度 End - to - end	
	OD <sub>1</sub>		OD <sub>2</sub>		C		M(1)		H	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
30x26	30	762	26	660.4	22	559	21.5	546	24	610
30x24	30	762	24	609.6	22	559	21	533	24	610
30x22	30	762	22	558.8		559	20.5	521	24	610
30x20	30	762	20	508	22	559	20	508	24	610
30x18	30	762	18	457.2	22	559	19.5	495	24	610
30x16	30	762	16	406.4	22	559	19	483	24	610
30x14	30	762	14	355.6	22	559	19	483	24	610
30x12	30	762	12.75	323.8	22	559	18.62	473	24	610
30x10	30	762	10.75	273	22	559	18.12	460	24	610
32x30	32	813	30	762	23.5	597	23	584	24	610
32x28	32	813	28	711.2	23.5	597	22.5	572	24	610
32x26	32	813	26	660.4	23.5	597	22.5	572	24	610
32x24	32	813	24	609.6	23.5	597	22	559	24	610
32x22	32	813	22	558.8	23.5	597	21.5	546	24	610
32x20	32	813	20	508	23.5	597	21	533	24	610
32x18	32	813	18	457.2	23.5	597	20.5	521	24	610
32x16	32	813	16	406.4	23.5	597	20	508	24	610
32x14	32	813	14	355.6	23.5	597	20	508	24	610
34x32	34	864	32	812.8	25	635	24.5	622	24	610
34x30	34	864	30	762	25	635	24	610	24	610
34x28	34	864	28	711.2	25	635	23.5	597	24	610
34x26	34	864	26	660.4	25	635	23.5	597	24	610
34x24	34	864	24	609.6	25	635	23	584	24	610
34x22	34	864	22	558.8	25	635	22.5	572	24	610
34x20	34	864	20	508	25	635	22	559	24	610
34x18	34	864	18	457.2	25	635	21.5	546	24	610
34x16	34	864	16	406.4	25	635	21	533	24	610
36x34	36	914	34	863.6	26.5	673	26	660	24	610
36x32	36	914	32	812.8	26.5	673	25.5	648	24	610
36x30	36	914	30	762	26.5	673	25	635	24	610
36x28	36	914	28	711.2	26.5	673	24.5	622	24	610
36x26	36	914	26	660.4	26.5	673	24.5	622	24	610
36x24	36	914	24	609.6	26.5	673	24	610	24	610
36x22	36	914	22	558.8	26.5	673	23.5	597	24	610
36x20	36	914	20	508	26.5	673	23	584	24	610
36x18	36	914	18	457.2	26.5	673	22.5	572	24	610
36x16	36	914	16	406.4	26.5	673	22	559	24	610
38x36	38	965	36	914.4	28	711	28	711	24	610
38x34	38	965	34	863.6	28	711	27.5	698	24	610


NOTE:(1)Outlet dimensions M for run sizes NPS 14 and larger is recommended but not required.

# REDUCING TEES AND CONCENTRIC & ECCENTRIC REDUCERS


异径三通和同心，偏心异径管



异径三通  
Reducing Outlet Tee



同心大小头  
Concentric Reducers



偏心大小头  
Eccentric Reducers

## ASME B16.9


公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel				中心至端面 Center - to - end				长度 End - to - end	
	OD <sub>1</sub>		OD <sub>2</sub>		C		M(1)		H	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
38x32	38	965	32	812.8	28	711	27	686	24	610
38x30	38	965	30	762	28	711	26.5	673	24	610
38x28	38	965	28	711.2	28	711	25.5	648	24	610
38x26	38	965	26	660.4	28	711	25.5	648	24	610
38x24	38	965	24	609.6	28	711	25	635	24	610
38x22	38	965	22	558.8	28	711	24.5	622	24	610
38x20	38	965	20	508	28	711	24	610	24	610
38x18	38	965	18	457.2	28	711	23.5	597	24	610
40x38	40	1016	38	965.2	29.5	749	29.5	749	24	610
40x36	40	1016	36	914.4	29.5	749	29	737	24	610
40x34	40	1016	34	863.6	29.5	749	28.5	724	24	610
40x32	40	1016	32	812.8	29.5	749	28	711	24	610
40x30	40	1016	30	762	29.5	749	27.5	698	24	610
40x28	40	1016	28	711.2	29.5	749	27	673	24	610
40x26	40	1016	26	660.4	29.5	749	26.5	673	24	610
40x24	40	1016	24	609.6	29.5	749	26.5	660	24	610
40x22	40	1016	22	558.8	29.5	749	26	648	24	610
40x20	40	1016	20	508	29.5	749	25	635	24	610
40x18	40	1016	18	457.2	29.5	749	24.5	622	24	610
42x40	42	1067	40	1016	30	762	28	711	24	610
42x38	42	1067	38	965.2	30	762	28	711	24	610
42x36	42	1067	36	914.4	30	762	28	711	24	610
42x34	42	1067	34	863.6	30	762	28	711	24	610
42x32	42	1067	32	812.8	30	762	28	711	24	610
42x30	42	1067	30	762	30	762	28	711	24	610
42x28	42	1067	28	711.2	30	762	27.5	698	24	610
42x26	42	1067	26	660.4	30	762	27.5	698	24	610
42x24	42	1067	24	609.6	30	762	26	660	24	610
42x22	42	1067	22	558.8	30	762	26	660	24	610
42x20	42	1067	20	508	30	762	26	660	24	610
42x18	42	1067	18	457.2	30	762	25.5	648	24	610
42x16	42	1067	16	406.4	30	762	25	635	24	610
44x42	44	1118	42	1066.8	32	813	30	762	24	610
44x40	44	1118	40	1016	32	813	29.5	749	24	610
44x38	44	1118	38	965.2	32	813	29	737	24	610
44x36	44	1118	36	914.4	32	813	28.5	724	24	610
44x34	44	1118	34	863.6	32	813	28.5	724	24	610
44x32	44	1118	32	812.8	32	813	28	711	24	610
44x30	44	1118	30	762	32	813	28	711	24	610

NOTE:(1)Outlet dimensions M for run sizes NPS 14 and larger is recommended but not required.


# REDUCING TEES AND CONCENTRIC & ECCENTRIC REDUCERS

异径三通和同心，偏心异径管


不锈钢法兰管件 优质供应商  
Quality Supplier Of Stainless Steel  
Flange Pipe Fittings



异径三通  
Reducing Outlet Tee



同心大小头  
Concentric Reducers




偏心大小头  
Eccentric Reducers


## ASME B16.9

公称通径 Nominal Pipe Size (NPS)	端部外径 Outside Diameter At Bevel				中心至端面 Center - to - end				长度 End - to - end	
	OD <sub>1</sub>		OD <sub>2</sub>		C		M(1)		H	
	IN	MM	IN	MM	IN	MM	IN	MM	IN	MM
44x28	44	1118	28	711.2	32	813	27.5	698	24	610
44x26	44	1118	26	660.4	32	813	27.5	698	24	610
44x24	44	1118	24	609.6	32	813	27.5	698	24	610
44x22	44	1118	22	558.8	32	813	27	698	24	610
44x20	44	1118	20	508	32	813	27	698	24	610
46x44	46	1168	44	1117.6	33.5	851	34.5	800	28	711
46x42	46	1168	42	1066.8	33.5	851	31	787	28	711
46x40	46	1168	40	1016	33.5	851	30.5	775	28	711
46x38	46	1168	38	965.2	33.5	851	30	762	28	711
46x36	46	1168	36	914.4	33.5	851	30	762	28	711
46x34	46	1168	34	863.6	33.5	851	29.5	749	28	711
46x32	46	1168	32	812.8	33.5	851	29.5	749	28	711
46x30	46	1168	30	762	33.5	851	29	737	28	711
46x28	46	1168	28	711.2	33.5	851	29	737	28	711
46x26	46	1168	26	660.4	33.5	851	29	737	28	711
46x24	46	1168	24	609.6	33.5	851	28.5	724	28	711
46x22	46	1168	22	558.8	33.5	851	28.5	724	28	711
48x46	48	1219	46	1168.4	35	889	33	838	28	711
48x44	48	1219	44	1117.6	35	889	33	838	28	711
48x42	48	1219	42	1066.8	35	889	32	813	28	711
48x40	48	1219	40	1016	35	889	32	813	28	711
48x38	48	1219	38	965.2	35	889	32	813	28	711
48x36	48	1219	36	914.4	35	889	31	787	28	711
48x34	48	1219	34	863.6	35	889	31	787	28	711
48x32	48	1219	32	812.8	35	889	31	787	28	711
48x30	48	1219	30	762	35	889	30	762	28	711
48x28	48	1219	28	711.2	35	889	30	762	28	711
48x26	48	1219	26	660.4	35	889	30	762	28	711
48x24	48	1219	24	609.6	35	889	29	737	28	711
48x22	48	1219	20	558.8	35	889	29	737	28	711

NOTE:(1)Outlet dimensions M for run sizes NPS 14 and larger is recommended but not required.



项目 Item	内容 Description
标准 Standard	按DL/T515《电站弯管》、SY5257《钢制弯管》执行，或按顾客提出的标准或技术要求执行 according to DL/T515 《power station Bend》, SY5257 《steel Bend》, or customer's technical drawings
材料 Material	碳钢、合金钢、不锈钢 carbon steel, alloy steel, stainless steel
弯曲半径 R Bend Radius R	$R \leq 6000\text{mm} \geq$ , 且 $R \geq 3D$ (用R等于3D、4D、5D、6D、7D、8D、9D、10D来表示弯曲半径, D为管子外径) $R \geq 3D$ ( $R=3D、4D、5D、6D、7D、8D、9D、10D$ ) D: outside diameter
弯曲半径 $\theta$ Bend Angle $\theta$	常用为15°、45°、60°、90°、135°、和180°、, 也可以按顾客提出的角度弯制 normally 15°、30°、45°、60°、90°、135°、80° or at customer's option
直段长度 L Length of Straight L	弯管两端直段长度一般在300mm-1500mm,由顾客确定长度的大小 normally between 300mm and 1500mm in length of straight, It is at customer's option
外径 D Outside Diameter D	$D \leq 1220\text{mm}$
壁厚 T Wall Thickness T	$T \leq 120\text{mm}$
端部坡口 End Bevel	按对焊管件焊端坡口结构型执行 according to welding bevel of butt welding fitting
重量 Weight	重量/kg = $\frac{0.0433(D-T)TR\theta}{100000}$ + L(双直管段重量) Weight/kg = $\frac{0.0433(D-T)TR\theta}{100000}$ + L(Weight of Double Sides Straight Length)




公差表 Tolerance table

mm

所有管件 Parts of all pipes					90° 45° 弯头、三通、四通 结构尺寸 Elbows, Tees Center-to-End Dimension	异径接头 翻边管高度 Reducer Lao joint Stub Ensd Overall Length	管帽 Caps	180° 弯头 elbow piece		
公称口径 Nominal diaeter		端面外径 Outside Diameter at Bevel	端部内径 Inside Diameter at Bevel	壁厚 Thickness	ABC	HF	高度 Overall Length E E1	中心距 center-to- center dimension O	高度 Back-to- Face dimension K	端面误差 Alignment of Ends U
DN	NPS	OD D1 D2	ID	T	ABC	HF	E E1	O	K	U
15-65	1/2-2 1/2	+1.6-0.8	0.8	壁厚 Thickness T 不小于 工程壁厚 的87.5% No less than 87.5% of nominal wall thickness	2	2	3	6	6	1
80-90	3-3 1/2	+1.6	1.6		2	2	3	6	6	1
100	4	+1.6	1.6		2	2	3	6	6	1
125-200	5-8	+2.4-1.6	1.6		2	2	6	6	6	1
250-450	10-18	+4.0-3.2	3.2		2	2	6	10	6	2
500-600	20-24	+6.4-4.8	4.8		2	2	6	10	6	2
650-750	26-30	+6.4-4.8	4.8		3	5	10	-	-	-
800-1200	37-48	+6.4-4.8	4.8		5	5	10	-	-	-
13000-15000	52-60	+9.5-6.4	6.4		9.5	-	-	-	-	-
16000-17000	64-68	+12-9.5	9.5		12	-	-	-	-	-
18000-2000	72-80	+16-12	12	16	-	-	-	-	-	

公称口径 Nominal Pipe Size		DN	15-100	125-200	250-300	350-400	450-600	650-750	800-1050	1100-1200	1300-1500
		NPS	1/2-4	5-8	10-12	14-16	18-24	26-30	32-42	44-48	52-60
倾斜度偏差 Angularity tolerance	角度偏移 Off Angle	Q	1	2	3	3	4	5	5	5	6.4
	平面偏移 Off Plian	P	2	4	5	6	10	10	13	19	20

规定的对焊管件端坡口的结构型式 ASME/ANSI B16.9 B16.28  
End Preperation of Butt-welding Fittings to ASME/ANSI B16.9 B16.28



# OUTSIDE DIAMETER AND WALL THICKNESS TABLE

## 外径和壁厚表

公称通径 Nominal Pipe Size	外径 Outside Diameter		公称壁厚 T Nominal Wall Thickness															
	DN	A	B	SCH 5s	SCH 10s	SCH 20s	LG	SCH 20	SCH 30	STD	SCH 40	SCH 60	XS	SCH 80	SCH 100	SCH 120	SCH 140	SCH 160
15	21.3	18	1.6	2.1	2.6	-	-	-	-	2.9	-	-	3.6	-	-	-	-	4.5
20	26.9	25	1.6	2.1	2.6	-	-	-	-	2.9	-	-	4.0	-	-	-	-	5.6
25	33.7	32	1.6	2.8	3.2	-	-	-	-	3.2	-	-	4.5	-	-	-	-	6.3
32	42.4	38	1.6	2.8	3.2	-	-	-	-	3.6	-	-	5.0	-	-	-	-	6.3
40	48.3	45	1.6	2.8	3.2	-	-	-	-	3.6	-	-	5.0	-	-	-	-	7.1
50	60.3	57	1.6	2.8	3.6	-	3.2	-	-	4.0	-	-	5.6	-	-	-	-	8.8
65	76.1(73)	76	2.0	3.0	3.6	-	4.5	-	-	5.0	-	-	7.1	-	-	-	-	10.0
80	88.9	89	2.0	3.0	4.0	-	4.5	-	-	5.6	-	-	8.0	-	-	-	-	11.0
90	101.6	-	2.0	3.0	4.0	-	4.5	-	-	5.6	-	-	8.0	-	-	-	-	12.5
100	114.3	108	2.0	3.0	4.0	-	5.0	-	-	5.9	-	-	8.8	-	11.0	-	-	14.2
125	139.7	133	2.9	3.4	5.0	-	5.0	-	-	6.3	-	-	10.0	-	12.5	-	-	16.0
150	168.3	159	2.9	3.4	5.0	-	5.6	-	-	7.1	-	-	11.0	-	14.2	-	-	17.5
200	219.1	219	2.9	4.0	6.3	-	6.3	7.1	-	8.0	10.0	-	12.5	16.0	17.5	20.0	22.2	22.2
250	273.0	273	3.6	4.0	6.3	-	6.3	8.0	-	8.8	12.5	-	16.0	17.5	22.2	25.0	28.0	28.0
300	323.9	325	4.0	4.5	6.3	-	6.3	8.8	-	10.0	14.2	-	17.5	22.2	25.0	28.0	32.0	32.0
350	355.6	377	4.0	5.0	-	8.0	8.0	10.0	10.0	11.0	16.0	13.0	20.0	25.8	28.0	32.0	36.0	36.0
400	406.4	426	4.0	5.0	-	8.0	8.0	10.0	10.0	12.5	17.5	13.0	22.2	28.0	30.0	36.0	40.0	40.0
450	457.2	478	4.0	5.0	-	8.0	8.0	11.0	10.0	14.2	20.0	13.0	25.0	30.0	36.0	40.0	45.0	45.0
500	508.0	529	5.0	5.6	-	8.0	10.0	12.5	10.0	16.0	20.0	13.0	28.0	32.0	40.0	45.0	50.0	50.0
550	559	-	5.0	5.6	-	8.0	-	-	10.0	-	-	13.0	30.0	-	-	-	-	-
600	610	630	5.6	6.3	-	8.0	-	-	10.0	17.5	-	13.0	32.0	-	-	-	-	-
650	660	-	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
700	711	720	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
750	762	-	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
800	813	820	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
850	864	-	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
900	914	920	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
950	965	-	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
1000	1016	1020	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
1050	1067	-	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
1100	1118	1120	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
1150	1168	-	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-
1200	1220	1220	-	-	-	8.0	-	-	10.0	-	-	13.0	-	-	-	-	-	-

SCH5s、10s、20s用于不锈钢管件  
SCH5s、10s、20s applies for stainless steel fittings.

# OUTSIDE DIAMETER AND WALL THICKNESS TABLE

## 外径和壁厚表

不锈钢法兰管件 优质供应商  
Quality Supplier Of Stainless Steel  
Flange Pipe Fittings

公称口径 Nominal Pipe Size	外径 Outside Diameter	公称壁厚 T Nominal Wall Thickness						
		公称压力 MPa Nominal Pressure						
DN	D	10	1.6	2.5	4.0	6.4	10.0	16.0
15	18	3	3	3	3	3	-	-
20	25	3	3	3	3	3	-	-
25	32	3.5	3.5	3.5	3.5	3.5	4.5	6.5
32	38	3.5	3.5	3.5	3.5	3.5	4.5	7
40	45	3.5	3.5	3.5	3.5	3.5	4.5	7
50	57	3.5	3.5	3.5	3.5	3.5	5	7
65	76	4	4	4	4	4.5	6	8
80	89	4	4	4	4	5	7	9
100	108	4	4	4	4	6	8	10
125	133	4	4	4	4	7	10	11
150	159	4.5	4.5	4.5	4.5	8	12	14
200	219	6	6	6	7	10	14	18
250	273	8	8	8	8	11	16	24
300	325	8	8	8	9	12	18	28
350	377	9	9	9	9	15	22	30
400	428	9	9	9	11	16	24	34
450	478	9	9	10	12	18	26	38
500	529	9	9	11	14	20	28	40
600	630	9	9	12	15	22	-	-

# OUTSIDE DIAMETER AND WALL THICKNESS TABLE

## 外径和壁厚表



公称通径 Nominal Pipe Size		外径 Outside Diameter		公称壁厚 T Nominal Wall Thickness																	
DN	NPS	D	D	SCH 5s	SCH 10s	SCH 10	SCH 20	SCH 30	SCH 40s	STD	SCH 40	SCH 60	SCH 80s	XS	SCH 80	SCH 100	SCH 120	SCH 140	SCH 160	XXS	
6	1/8	10.3	10.3	-	1.24	-	-	-	1.73	1.73	1.73	-	2.41	2.41	2.41	-	-	-	-	-	-
8	1/4	13.7	13.7	-	1.65	-	-	-	2.24	2.24	2.24	-	3.02	3.02	3.02	-	-	-	-	-	-
10	3/8	17.1	17.1	-	1.65	-	-	-	2.31	2.31	2.31	-	3.20	3.20	3.20	-	-	-	-	-	-
15	1/2	21.3	21.3	1.65	2.11	-	-	-	2.77	2.77	2.77	-	3.73	3.73	3.73	-	-	-	-	4.78	7.47
20	3/4	26.7	26.7	1.65	2.11	-	-	-	2.87	2.87	2.87	-	3.91	3.91	3.91	-	-	-	-	5.56	7.82
25	1	33.4	33.4	1.65	2.77	-	-	-	3.38	3.38	3.38	-	4.55	4.55	4.55	-	-	-	-	6.35	9.09
32	1 1/4	42.2	42.2	1.65	2.77	-	-	-	3.56	3.56	3.56	-	4.85	4.85	4.85	-	-	-	-	6.35	9.70
40	1 1/2	48.3	48.3	1.65	2.77	-	-	-	3.68	3.68	3.68	-	5.08	5.08	5.08	-	-	-	-	7.14	10.15
50	2	60.3	60.3	1.65	2.77	-	-	-	3.91	3.91	3.91	-	5.54	5.54	5.54	-	-	-	-	8.74	11.07
65	2 1/2	73.0	73.0	2.11	3.05	-	-	-	5.16	5.16	5.16	-	7.01	7.01	7.01	-	-	-	-	9.53	14.02
80	3	88.9	88.9	2.11	3.05	-	-	-	5.49	5.49	5.49	-	7.62	7.62	7.62	-	-	-	-	11.13	15.24
90	3 1/2	101.6	101.6	2.11	3.05	-	-	-	5.74	5.74	5.74	-	8.08	8.08	8.08	-	-	-	-	-	-
100	4	114.3	114.3	2.11	3.05	-	-	-	6.02	6.02	6.02	-	8.56	8.56	8.56	-	11.13	-	-	13.49	17.12
125	5	141.3	141.3	2.77	3.40	-	-	-	6.55	6.55	6.55	-	9.53	9.53	9.53	-	12.70	-	-	15.88	19.05
150	6	168.3	168.3	2.77	3.40	-	-	-	7.11	7.11	7.11	-	10.97	10.97	10.97	-	14.27	-	-	18.26	21.95
200	8	219.1	219.1	2.77	3.76	-	6.35	7.04	8.18	8.18	8.18	10.31	12.70	12.70	12.70	15.09	18.26	20.62	23.01	22.23	25.40
250	10	273.1	273.1	3.40	4.19	-	6.35	7.80	9.27	9.27	9.27	12.70	12.70	12.70	15.09	18.26	21.44	25.40	28.58	25.40	25.40
300	12	323.9	323.9	3.96	4.57	-	6.35	8.38	9.53	9.53	10.31	14.27	12.70	12.70	17.48	21.44	25.40	28.58	33.32	25.40	25.40
350	14	355.6	355.6	3.96	4.78	6.35	7.92	9.53	-	9.53	11.13	15.09	-	12.70	19.05	23.83	27.79	31.75	35.71	-	-
400	16	406.4	406.4	4.19	4.78	6.35	7.92	9.53	-	9.53	12.70	16.66	-	12.70	21.44	26.19	30.96	36.53	40.49	-	-
450	18	457.2	457.2	4.19	4.78	6.35	7.92	11.13	-	9.53	14.27	19.05	-	12.70	23.83	29.36	34.93	39.67	45.24	-	-
500	20	508	508	4.78	5.54	6.35	9.53	12.70	-	9.53	15.09	20.62	-	12.70	26.19	32.54	38.10	44.45	50.01	-	-
-	22	559	559	4.78	5.54	6.35	9.53	12.70	-	9.53	-	22.23	-	12.70	28.58	34.93	41.28	47.63	53.98	-	-
600	24	610	610	5.54	6.35	6.35	9.53	14.27	-	9.53	17.48	24.61	-	12.70	30.96	38.89	46.02	52.37	59.54	-	-
-	26	660	660	-	-	7.92	12.70	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
700	28	711	711	-	-	7.92	12.70	15.88	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
-	30	762	762	6.35	7.92	7.92	12.70	15.88	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
800	32	813	813	-	-	7.92	12.70	15.88	-	9.53	17.48	-	-	12.70	-	-	-	-	-	-	-
-	34	864	864	-	-	7.92	12.70	15.88	-	9.53	17.48	-	-	12.70	-	-	-	-	-	-	-
900	36	914	914	-	-	7.92	12.70	15.8	-	9.53	19.05	-	-	12.70	-	-	-	-	-	-	-
-	38	965	965	-	-	-	-	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
1000	40	1016	1016	-	-	-	-	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
-	42	1067	1067	-	-	-	-	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
1100	44	1118	1118	-	-	-	-	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
-	46	1168	1168	-	-	-	-	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-
1200	48	1219	1219	-	-	-	-	-	-	9.53	-	-	-	12.70	-	-	-	-	-	-	-

SCH5s、10s、40s、80s用于不锈钢管件  
SCH15s、10s、40s、80s applies for stainless steel fittings.

# COMMON MATERIAL OF PRESSURE PIPE FITTING IN CHINA

## 中国压力管道管件常用材料

不锈钢法兰管件 优质供应商

Quality Supplier Of Stainless Steel Flange Pipe Fittings

牌号 Grade	标准号 Standard and Code	类型 Type	化学成分 Chemical Compositin %, max										力学性能 Mechanical Properties						
			C	Si	Mn	Cr	Ni	Cu	Mo	P	S	Other	φ b MPa min	φ a MPa min	φ 5 % min	HB max	Other		
奥氏体 不锈钢 Austenitic Stainless Steel	00Cr17Ni14Mo2	棒BAR	0.030	1.00	2.00	16.00-18.00	12.00-15.00	2.00-3.00	0.035	0.030	-	-	-	480	177	40	187	φ %: 60	
	00Cr17Ni14Mo2	板PLATE	0.030	1.00	2.00	16.00-18.00	12.00-15.00	2.00-3.00	0.035	0.030	-	-	-	480	177	40	187	-	
	00Cr17Ni14Mo2	管PIPE	0.030	1.00	2.00	16.00-18.00	12.00-15.00	2.00-3.00	0.035	0.030	-	-	-	480	175	35	-	-	
	00Cr19Ni10	棒BAR	0.030	1.00	2.00	18.00-20.00	8.00-12.00	-	0.035	0.030	-	-	-	480	177	40	187	φ %: 60	
	00Cr19Ni10	板PLATE	0.030	1.00	2.00	18.00-20.00	8.00-12.00	-	0.035	0.030	-	-	-	480	177	40	187	-	
	00Cr19Ni10	管PIPE	0.030	1.00	2.00	18.00-20.00	8.00-12.00	-	0.030	0.030	-	-	-	480	175	35	-	-	
	0Cr17Ni12Mo2	棒BAR	0.08	1.00	2.00	16.00-18.50	10.00-14.00	2.00-3.00	0.035	0.030	-	-	-	520	205	40	187	φ %: 60	
	0Cr17Ni12Mo2	板PLATE	0.08	1.00	2.00	16.00-18.00	10.00-14.00	2.00-3.00	0.035	0.030	-	-	-	520	205	40	187	-	
	0Cr17Ni12Mo2	管PIPE	0.08	1.00	2.00	16.00-18.50	10.00-14.00	2.00-3.00	0.035	0.030	-	-	-	520	205	35	-	-	
	0Cr18Ni9	棒BAR	0.07	1.00	2.00	17.00-19.00	8.00-11.00	-	0.035	0.030	-	-	-	520	205	40	187	φ %: 60	
	0Cr18Ni9	板PLATE	0.07	1.00	2.00	17.00-19.00	8.00-11.00	-	0.035	0.030	-	-	-	520	205	40	187	-	
	0Cr18Ni9	管PIPE	0.07	1.00	2.00	17.00-19.00	8.00-11.00	-	0.035	0.030	-	-	-	520	205	35	-	-	
	0Cr18Ni10Ti	棒BAR	0.08	1.00	2.00	17.00-19.00	9.00-12.00	-	0.035	0.030	-	-	-	520	205	40	187	φ %: 50	
	0Cr18Ni10Ti	板PLATE	0.08	1.00	2.00	17.00-19.00	9.00-12.00	-	0.035	0.030	-	-	-	520	205	40	187	-	
	0Cr18Ni10Ti	管PIPE	0.08	1.00	2.00	17.00-19.00	9.00-12.00	-	0.030	0.030	-	-	-	520	205	35	-	-	
	0Cr18Ni12Mo2Ti	棒BAR	0.08	1.00	2.00	16.00-19.00	11.00-14.00	1.80-2.50	0.035	0.030	-	-	-	530	205	40	187	φ %: 55	
	0Cr18Ni12Mo2Ti	板PLATE	0.08	1.00	2.00	16.00-19.00	11.00-14.00	1.80-2.50	0.035	0.030	-	-	-	530	205	37	187	-	
	0Cr18Ni12Mo2Ti	管PIPE	0.08	1.00	2.00	16.00-19.00	11.00-14.00	1.80-2.50	0.035	0.030	-	-	-	530	205	35	-	-	
	双相 不锈钢 Biphase Stainless Steel	1Cr18Ni9	板PLATE	0.15	1.00	2.00	17.00-19.00	8.00-10.00	-	0.035	0.030	-	-	-	520	205	40	187	-
		1Cr18Ni9	管PIPE	0.15	1.00	2.00	17.00-19.00	8.00-10.00	-	0.035	0.030	-	-	-	520	205	35	-	-
0Cr26Ni5Mo2		棒BAR	0.08	1.00	1.50	23.00-28.00	3.00-6.00	1.00-3.00	0.035	0.030	-	-	-	590	390	18	277	φ %: 40	
0Cr26Ni5Mo2		板PLATE	0.08	1.00	1.50	23.00-28.00	3.00-6.00	1.00-3.00	0.035	0.030	-	-	-	590	390	18	277	-	
0Cr26Ni5Mo2		管PIPE	0.08	1.00	1.50	23.00-28.00	3.00-6.00	1.00-3.00	0.035	0.030	-	-	-	590	390	18	-	-	
低温钢 Low Temperature Steel	00Cr18Ni5Mo3Si2	棒BAR	0.030	1.30-2.00	1.00-2.00	18.00-19.50	4.50-5.50	2.50-3.00	0.035	0.030	-	-	-	590	390	20	-	φ %: 40	
	00Cr18Ni5Mo3Si2	板PLATE	0.030	1.30-2.00	1.00-2.00	18.00-19.5	4.5-5.5	2.5-3.0	0.030	0.030	-	-	-	590	390	20	-	-	
	09MnNiDR	板PLATE	0.012	0.15-0.50	1.20-1.60	0.25	0.30-0.80	0.08	0.025	0.020	-	-	-	440-570	290	22	-	Akv J: 27	
	16Mn	管PIPE	0.12-0.20	0.20-0.60	1.20-1.60	-	-	0.040	0.040	0.040	-	-	-	490-670	320	21	-	ak J/cm2: 59	
	16Mnq	板PLATE	0.20	0.20-0.55	1.20-1.60	0.30	0.30	0.10	0.035	0.030	-	-	-	510-655	345	21	-	ak J: 27	
16MnDR	板PLATE	0.20	0.15-0.50	1.20-1.60	0.25	0.40	0.08	0.030	0.025	-	-	-	490-620	315	21	-	ak J: 24		
16MnR	板PLATE	0.20	0.20-0.55	1.20-1.60	0.30	0.30	-	0.035	0.030	-	-	-	510-640	345	21	-	ak J: 31		